



सिंहदरबार,
काठमाडौं, नेपाल ।

चलानी नं.:- ७१८

मिति:- २०८०/०७/१९

श्री भौतिक पूर्वाधार विकास मन्त्रालय,
मधेश प्रदेश, जनकपुरधाम ।

श्री भौतिक पूर्वाधार तथा शहरी विकास मन्त्रालय,
कर्णाली प्रदेश, सुर्खेत ।

श्री भौतिक पूर्वाधार विकास मन्त्रालय,
सुदूरपश्चिम प्रदेश, धनगढी ।

विषय:- नमूना Standards, Norms and specifications for Roads and bridges construction for provincial Roads पठाइएको सम्बन्धमा ।

उपरोक्त विषयमा स्थानीय पूर्वाधार विभागबाट प्रादेशिक तथा स्थानीय सडक सुधार कार्यक्रम कार्यान्वयनका लागि Standards, Norms and Specification for Road and Bridge construction for provincial Roads सम्बन्धी नमूना दस्तावेज (Reference documents) मन्त्रालयको मिति २०८०/०७/१७ को (सचिवस्तरीय) निर्णय अनुसार यसै पत्रसाथ संलग्न गरी पठाइएको व्यहोरा अनुरोध छ।

बोधार्थ:-

१. श्री स्थानीय पूर्वाधार विभाग, श्रीमहल, पुलचोक ललितपुर ।
२. श्री प्रादेशिक तथा स्थानीय सडक सुधार कार्यक्रम, श्रीमहल, पुलचोक ललितपुर ।

.....
निरुपम मिश्र
सि.डि.ई

क्षीयो तथा विप्रप्र श्रावः—

2nd
2020/06/24

६. श्री अशोकजी
 श्री प्रकाश शर्मा
 श्री RCLP का
 एमक जगदीश
 ६/११



Government of Nepal
Ministry of Urban Development
Department of Local Infrastructure (DoLI)
Provincial and Local Roads Improvement Program (PLRIP)
Central Program Coordination Unit (CPCU)
Shreemahal, Lalitpur

**Standards, Norms
and Specifications for Road & Bridge
Construction
for
Provincial Roads**

June 2023

me
2023



CONTENTS


1	INTRODUCTION.....	1
1.1	Background.....	1
1.2	Recommendation of Road/ Bridges Design and Construction Standards and Specifications.....	1
2	Review of Documents.....	1
2.1	Road and Bridge Standards.....	1
2.1.1	Nepal Rural Road Standards (DoLIDAR, 2014).....	1
2.1.2	Nepal Urban Road Standards (DUDBC, 2019).....	1
2.1.3	Nepal Road Standards (DoR, 2013).....	1
2.1.4	Nepal Bridge Standards (DoR 2010).....	1
2.2	Standard Specifications for Road and Bridge Works.....	1
2.2.1	Standard Specifications for Road and Bridge Works (DoR, 2016).....	1
2.2.2	Technical Specifications for Agricultural and Rural Roads (DoLIDAR, 1998).....	1
2.3	Norms for Rate Analysis.....	2
2.3.1	Norms for Rate Analysis of Road and Bridge Works (DoR, 2018).....	2
2.3.2	Work Norms for Agricultural and Rural Roads (DoLIDAR, 1998).....	2
2.3.3	Other Norms.....	2
3	Recommendations for PLRIP.....	2
3.1	Road Standards.....	2
3.2	Bridge Standards.....	2
3.3	Norms for Rate Analysis.....	2
3.4	Specifications.....	2

Appendix A

Provincial Road Standards, 2023

[Handwritten signature]

[Handwritten signature]
शरत प्रसाद अयाँल
सहानिर्देशक



INTRODUCTION

1.1 Background

There is often a lack of coordination and uniformity in the adoption of road standards and specifications. DoLI has an interim road standard, 2019 prepared for the use of the Provincial Government and Local-level entities. However, it is noted that each Province is preparing Province Road Act, and road and bridge standards. While the provinces have made progress with their Province Road Act, the Federal Government has yet to approve the Nepal Road Act compatible with federalism and clarifying provincial and local roads, and ownership, which the earlier Public Road Act 1974 does not cater to. Also, instead of a selection of appropriate road standards for the projected traffic, the provinces and municipalities are considering much higher standard roads in terms of both the road width as well as pavement type. In the case of Specification and Norms for road and bridge works, it is noted that the provinces and the municipalities are found to follow the DoR documents as the revised Norms and Specification from DoLI for local/provincial roads is yet to be approved.

1.2 Recommendation of Road/ Bridges Design and Construction Standards and Specifications

This document provides review of various standards, specifications and norms for road, bridge design and construction and recommendations for DoLI has been prepared.

2 Review of Documents

2.1 Road and Bridge Standards

2.1.1 Nepal Rural Road Standards (DoLIDAR, 2014)

The Nepal Rural Road Standard (NRRS) was first introduced in 1998 (2055 BS) and 2nd revision was published in 2014 (2071 BS) by the DoLIDAR. The standard provides the road classification and geometric standards for rural roads (then district roads & village roads) in Nepal.

2.1.2 Nepal Urban Road Standards (DUDBC, 2019)

The Nepal Urban Road Standard (NURS) was prepared by DUDBC in 2019 (2076 BS). It provides the standard for classification, geometric design, cross-section elements, etc. for the urban roads in Nepal.

2.1.3 Nepal Road Standards (DoR, 2013)

The Nepal Road Standard published by DoR in 2013 (2070 BS) provides road classification, road design capacities, geometric design standards, etc. It is second revision of the road standard originally published in 1970 (2027 BS) and first revision was published in 1988 (2045 BS).

2.1.4 Nepal Bridge Standards (DoR 2010)

This standard provides standard for the bridge works including hydraulic modeling, free board, and bridge geometry. DoR also has produced standard drawings for bridges in 2015 which includes standard drawings of bridges from 15m span to 40m span.

2.2 Standard Specifications for Road and Bridge Works

2.2.1 Standard Specifications for Road and Bridge Works (DoR, 2016)

The specification was published by DoR in 2001 (2058 BS) and later revised in 2016 (2073 BS). The latest version includes many items required for road and bridge construction. It also includes standards for various maintenance activities.

2.2.2 Technical Specifications for Agricultural and Rural Roads (DoLIDAR, 1998)

The specification covers many aspects of the rural road construction.



2.3 Norms for Rate Analysis

2.3.1 Norms for Rate Analysis of Road and Bridge Works (DoR, 2018)

The norms was published by DoR in 2018 (2075 BS) which is based on the specifications published in 2016. The norms include many items including mechanized earthwork excavation and also has simplified rate analysis for road construction works. It also has norms for road maintenance works.

2.3.2 Work Norms for Agricultural and Rural Roads (DoLIDAR, 1998)

The norms covers rate analysis for various work items described in the technical specifications for the agricultural and rural roads.

2.3.3 Other Norms

The Department of Urban Development and Building Construction (DUDBC) has published norms for rate analysis for building works. The Department of Water Resources and Irrigation (DWRI) also has published Rate Analysis Norms and Specifications for Irrigation, River Training & Study Works. The Department of Water Supply and Sewerage Management (DWSSM) also has published its own norms for rate analysis of water supply and sewerage management works. The Department of Forests and Soil Conservation (DFSC) also has its own norms for rate analysis of works related to forestry and soil conservation.

3 Recommendations for PLRIP

3.1 Road Standards

The NRS (2013) is comprehensive and can be adopted for PLRIP with minor modifications in certain parameters. The design standard prepared by DoLI for provincial highways and provincial roads is included in Appendix A. For the design of provincial roads, the standards for particular class of road will be determined by the traffic volume on the road (ADT).

3.2 Bridge Standards

The DoR Bridge Standard (2010) along with the standard drawings for bridges published in 2015 can be adopted for the PLRIP. Similarly, the LRBP also has prepared standard drawings of the bridges for DoLI.

The DoR standard drawings also include bridges for two lane carriageways (7.5m) with 1.5m footpath on each side and the LRBP standard includes bridges with 6.0m carriage way with 1.2m footpath on each side. Single lane bridges are not included in both the standards.

If proposed roads are double lane, DoR standard can be adopted and for single lane or intermediate lane roads, either DoR or DoLI standards can be adopted.

3.3 Norms for Rate Analysis

Norms for Rate Analysis of Road and Bridge Works (2018) published by Department of Roads covers all the work items to be included in roads and bridges construction. It also has norms for road maintenance works. So, Norms for Rate Analysis of Road and Bridge Works (DoR, 2018) can be adopted for PLRIP.

3.4 Specifications

Standard Specifications for Road and Bridge Works (DoR, 2016) published by DoR covers all the specifications required for road and bridge works in Nepal. The DoR has been using this specification for all the road and bridge works and RCIP under the DoLI is also using the same specification.

भरत प्र.
महानिदेशक

The Standard Specifications for Road and Bridge Works (DoR, 2016) can be included in the contract document as

Part A: Standard Specifications for Road and Bridge Works (DoR, 2016): This refers to the standard document and is available freely from DoR Website. Changes in this document should not be done.


www.dor.gov.np/home/publication/standard-specification-of-roads-and-bridges/force/standard-specifications-for-road-and-bridge-works-2-73

Part B: Special Provision to Standard Specifications: Any addition/substitute should be done here which generally depends on the nature of the project and specific items other than the standard specifications. It can also include additional specifications for survey (e.g. GPS based surveys), Drone Survey, Design software, etc. The RCIP and DoR has amended many clauses specific to the project.



[Handwritten signature]

[Handwritten signature]
भरत प्रसाद अर्याल
महानिर्देशक



Appendix A
Provincial Road Standards, 2023
(Adopted from Nepal Road Standards, 2013 with minor
modifications)

[Signature]

[Signature]

[Signature]
भरत प्रसाद अर्याल
महानिर्देशक

Provincial Road Standards, 2023 (Adopted from Nepal Road Standards, 2018 with minor modifications)

S.N	Design Parameters	Road Class - I	Road Class - II	Road Class - III	Road Class - IV	Remarks
1	Design capacity- in both directions (P.C.U per day)	>20000	5000-20000	2,000 - 5,000	<2,000	Refer Section 9B of NRS. Traffic figure are ADT expressed in PCU (forecast after 20 years).
2	Design speed (km per hour)	P-120 R-100 M-80 S-60	P-100 R-80 M-60 S-40	P-80 R-60 M-40 S-30	P-60 R-40 M-30 S-20	Refer Table 7 - 1 of NRS
3.a	No. of lanes	4 Min.	>=2	2	<2	Refer Annex 24.1, Table 24-1 of NRS
3.b	Roadway or Formation width (m)	Nx3.5+2Sw+Mw	Nx3.5+2Sw+3	9.0 to 11.0	5.5 to 8.5	Refer Section 11.4 & 11.8 of NRS n - Number of lane Sw - Shoulder width Mw - Median width
4	Lane width (m)	3.5	3.5	3.5	3.75* or 5.5	* 3m in difficult sections
5	Shoulder width, either side (m)	P, R - 3.75 M, S-2.5	P, R-2.5 M, S-2	P, R - 2 M, S - 1.0	P, R - 1.5 M, S - 0.75	Refer Section 11.2 and Table 24-1 of NRS. -Shoulder along road side drain shall be paved to prevent breakage of edge and erosion.
6	Total Right of Way (RoW) (m)	40	30	20	15	for provincial roads.
7	Setback distance from Road land boundary / RoW to Building line on either side (m)	6	6	6	6	Also Refer Section 3.7.3 of NURS 2076 for urban roads.
8	Minimum safe stopping distance (m)	P-260 R-190 M-130 S-80	P-190 R-130 M-80 S-50	P-130 R-80 M-50 S-30	P-80 R-50 M-30 S-20	Refer Table 8.1 of NRS Based on design speed
9	Lateral Clearance between roadside object and the edge of the shoulder (m)	See Comments	See Comments	See Comments	See Comments	Refer Section 11.9.2 of NRS
10	Minimum radius in horizontal curve (m)	110-1730	40-870	20 - 440	10-200	Refer Table 9-1 of NRS

भरत प्रसाद अर्याल
महानिदेशक



Minimum Spacing					
a.	Minimum spacing between hairpin bends (m)	60	80	100	Refer Section 9.3 and Table 9-3 of NRS
b.	Minimum radius of curve (m)	15	15	15	Refer Section 9.3 and Table 9-3 of NRS. In exceptional cases at steep mountainous and fragile terrain, a minimum radius of 10m may be adopted.
c.	Minimum Roadway width at apex (m)	Varies	Varies	Varies	Refer Table 9-4 of NRS
d.	Maximum gradient (%)	4	4	4	Refer Section 9.3 and Table 9-3 of NRS
e.	Maximum super elevation (%)	10	10	10	Refer Section 9.3 and Table 9-3 of NRS
f.	Minimum transition curve length (m)	Varies	Varies	Varies	Refer Section 9.2 and Table 9-2 of NRS
a.	Maximum Gradient (%)	P-4 R-5 M-6 S-7	P-5 R-6 M-7 S-9	P-6 R-7 M-9 S-10	P-7 R-9 M-10 S-12
b.	Grade Compensations	See Comments	See Comments	See Comments	See Comments
c.	Maximum (Critical) length of Grade (m)	P-4%, 600 R-5%, 450 M-6%, 400 S-7%, 300	P-5% 450 R-6% 400 M-7% 300 S-9% 200	P-6%, 400 R-7%, 300 M-9%, 200 S-10%, 150	P-7%, 300 R-9%, 200 M-10%, 150 S-12%, 150
13.	Maximum gradient at bridge approach (%)	2	3	4	5
14.	Minimum gradient on plain area roads (for better drainage) (%)	0.5	0.5	0.50	0.50
15.	Co-ordination of horizontal and vertical alignment	Varies	Varies	Varies	Varies
16.	Cross slope in carriageway camber (%)	5	5	5	5
	Gravel	4	4	4	4



भरत प्रसाद अर्याल
महानिदेशक

(Signature)

(Signature)

Refer Section 10.1.2 of NRS
Grade Compensation (%) = $(30+R)/R$ subject to a maximum of 75/R, R-
Radius of vertical curve.

Based on maximum (critical) gradient, refer Table 10.2 of NRS

Also Refer to Nepal Bridge Standards, 2067.

Refer Section 10.1.1 (e) of NRS.

Sharp horizontal curve should be avoided at or near the apex of the summit vertical curve or the lowest point of the valley curve.
Horizontal and vertical alignment should coincide with each other as far as possible and their length should be more or less equal. If this is difficult for any reason, the horizontal curve should be somewhat longer than the vertical curve.
The degree of curvature should be in proper balance with the gradients. Excessive curvature in a road with flat grades, do not constitute balanced design and should be avoided.
Also Refer Section 19 of NRS.

Refer Section 11.5 and Table 11-3 of NRS.
Undivided carriageway - both direction from the centre
Divided carriageway - unidirectional,

Kathmandu Metropolitan Office of Traffic Engineering and Transport Planning and Management									
S.N		Design Parameters		Roadway Width		Shoulder Width		Total Road Width	
				2.0	2.0	2.0	2.0	2.0	2.0
		Bituminous Seal Coat		1.5 to 2	1.5 to 2	1.5 to 2	1.5 to 2	1.5 to 2	1.5 to 2
17.	Passing Zone, Dimensions (width x length) (m x m)	NA	NA	NA	NA	NA*	NA*	NA*	NA*
	Bus Lay-bys, Dimension (width x length) (m x m)	3.75 * 15 N	3.75 * 15 N	3.75 * 15 N	3.75 * 15 N	3.75 * 15 N	3.75 * 15 N	3.75 * 15 N	3.75 * 15 N
18.	Carriageway width at culvert/bridge (m)	Full Width of Carriageway	Full Width of Carriageway	Full Width of Carriageway	Full Width of Carriageway	*	*	*	*
19.	Level of embankment above HFL (m)	*	*	*	*	*	*	*	*
20.	Traffic sign and road safety	*	*	*	*	*	*	*	*
21.	Median width (m)	3-5	3	NA	NA	NA	NA	NA	NA
Refer Section 11.3 of NRS. -Minimum median width of 5 m is recommended but a width of 3 m can be adopted in areas where land is restricted. -In mountainous and steep terrain, maximum possible width dictated by the topography should be provided -In extreme condition, simple barriers may be provided or individual carriageways could be designed at different levels.									

Notes: P-Plain, R-Rolling, M-Mountainous, S-Steep.

: Modifications are mentioned/typed in Boldface

Notes: P-Plain, R-Rolling, M-Mountainous, S-Steep.
: Modifications are mentioned/typed in Boldface

भरत प्रसाद अर्याल
महानिदेशक

