

### Invitation of Quotation/Proposals for LINAC Notice Published: September 23, 2025

B. P. Koirala Memorial Cancer Hospital invites detailed financial proposals with breakdown for the procurement of a Linear Accelerator (LINAC) Turn Key with the following details. This invitation is extended to capable and interested firms/companies, who must submit a comprehensive quotation, including a detailed Bill of Quantities (BoQ) and full specifications, along with all requisite legal and company documents, including a manufacturer's authorization.

Supply, Delivery, Installation and Commissioning of Linear Accelerator system (Turn Key )

S.N	Technical Specification
<b>A.</b>	AN OVERVIEW TO SPECIFICATIONS:-
	i. A digital Medical Linear Accelerator, Energy 6MV WFF/FFF capable of deliver 3DCRT, IMRT, VMAT
	with on board kvCBCT Imager.  ii. Proposed Machine (brand name) global lunched year must be 2015 or newer. Please specify
	iii. Proposed Machine (brand name) must be USFDA and CE certified.
B.	BASIC EQUIPMENT:-
1.	Energy:- Photon: 6 MV WFF/FFF
2.	Photon Beams Quality: As per BJR 11/17/25 .please specify
3.	Photon Dose rate:- The X-ray dose rate shall be variable in steps and shall be upto 500MU/min or more for 6 MV WFF/FFF
4.	RF Source:- Magnetron / Klystron, please specify
5.	Waveguide Type :- Standing / Travelling wave please specify
6.	Electron Gun:- Sealed / Unsealed
7.	Treatment Modes:- TSD / TAD
8.	Field Size:-
	i. Maximum: 28x28 cm <sup>2</sup> or more
	ii. Minimum: 1 x 1cm <sup>2</sup> or less.
9.	Beam Flatness/dynamic beam flatness:- $\pm$ 3% for FS 10x10 cm <sup>2</sup>
10.	Beam Symmetry:- $\pm 2$ % for $10x10$ cm <sup>2</sup>
11.	Gantry:-
	a. Rotation $\pm 180^{\circ}$ (360° total)
	b. Read out - Digital
	c. Accuracy dig-readout ±0.5°
	d. Control - Hand pendent and control-console
	e. Target - Axis Distance: $100 \pm 0.2$ cm
	f. ODI Accuracy ± 0.1 cm (Except Ring gantry Linear Accelerator)



S.N	Technical Specification
12.	Collimator:-
	a. Rotation: ± 90° about mid position/rotation range
	b. Control: Hand pendent and control- console
	c. Readout accuracy: ± 0.5°
	d. Collimator Rotation Isocentre ≤ 2 mm dia. Sphere
13.	Multi-leaf collimator (MLC):-
	a. No. of Leaves: at least 114 or above
	b. Leaf resolution: Central MLC leaves resolution must be ≤ 5mm at isocenter.
	c. Independent drives for each leaves.
14.	Treatment Couch:- 3DOF or more
15.	Wedges:- Motorized/Dynamic/Virtual Wedge (Not applicable to ring gantry Linac)
16.	Treatment delivery Capabilities:-3DCRT, IMRT, VMAT
17.	System shall have all safety interlocks, last person out switch, Door interlock, Emergency
	switches, Anti-collision sensor/system, Radiation beam ON/OFF indicator in bunker entrance
18.	Portal Imaging & Accessories:-MV imaging
19.	Portal dosimetry system
	or
	Equivalent system for pre-treatment IMRT/VMAT plan verification and QA (hardware and
	software). Must be a helical detector grid with more than twelve hundreds diode detectors, Tissue
	equivalent inserts must supply and system should compatible to supplied Linac.
20.	Treatment Planning System:-
	a) The treatment planning system: Two workstations (WS)
	b) Physician's contouring work station: 3WS with deformable image registration and auto
	fusion.
	c) Record & Verify System : 2WS
	d) TPS: The TPS should be of the latest version of optimization and planning algorithm &
	able to network with CT simulator, MRI/ PET and diagnostic CT system etc.
	e) Latest advanced hardware for Calculation and non-calculation workstation, minimum 23"
	LED/LCD monitor for workstations.
21.	Server (backup/restore):- fully integrated servers for data management and image
	management with sufficient back up capabilities.
22.	DICOM RT Data Import & Export Software should be supplied.
23.	Accessories:-
	a. CCTV / Camera four nos. two wide angle & two remote control with remote zoom & focus facility
	b. Laser alignment system – Green Color (4 nos.) / Inbuilt Inbore Laser alignment system (system
	color)
	c. An intercom (patient communication) system must be upplied.
	d. Compatible to proposed machine, Must supply a QA system for beam/machine
	parameter check.
	e. Last person out switch
C.	GENERAL SPECIFICATION
1.	General:-



S.N Technical Specification				
	Linear Accelerator must have the latest technology and should be fully computer			
	controlled with the latest state of art digital control system.			
2.	It shall be brand new machine. Machine manufacture date should not be more than two years			
	older from date of installation. Company shall provide certificate of trouble free operation of			
	proposed machine for two years from existing multiple users.			
3.	The supplier/bidder/company should provide one certified Service Engineer permanently			
	stationed for entire warranty period and must provide the necessary service/ maintenance			
	tools.			
4.	All the equipment/ accessories quoted and supplied should be of latest model. (Proof should			
	be enclosed in the form of press release/advertisement/certification by concerned			
	bodies/commitment in company letter head, etc.). If it is not latest, bid will not be qualified			
	from evaluation.			
5.	Company should give the undertaking for supply of spares till machine life.			
6.	Company should be responsible for installation, technical support to hospital responsible			
	physicist in machine acceptance tests, commissioning (if required).			
7.	Software updating should be provided free of cost for warranty and CMC period.			
8.	Installation and acceptance test performance support will be company's responsibility with			
	no additional cost (free of cost).			
9.	Warranty/Guarantee:-			
	i. From the date of machine handover to hospital of Linear accelerator systems including,			
	software, TPS shall have comprehensive warranty/guarantee for 5 years against			
	manufacturing defects of materials and workmanship. This also applies to the supplied			
	and installed supportive system such as chiller, UPS, Battery and HVAC system.			
	ii. Uptime of at least 95%. This time will be calculated 3 hours after reporting to engineer/			
	company by phone or emails till engineers hand over the machine for treatment. In case			
	of failure the compensation warranty period will be extended by 1:3 day ratio.			
10.	Comprehensive Maintenance Contract (CMC):-			
	a. After expiry of warranty/ guarantee period of 5 years, CMC charges must be			
	quoted for next 5 years on yearly basis (from 6th year to 10 <sup>th</sup> year) after expiry of			
	warranty for entire linear accelerator system along with TPS and including			
	supportive systems such as UPS, Battery, Chiller and HVAC.			
	b. The quoted CMC charges will be taken into consideration at the time of evaluation			
	(Financial) of the bid.			
	c. CMC charge, if taken as % of bid cost, should not include the cost of BoQ, i.e- cost of			
	civil, electrical work, dismantling cost, Training cost etc			
11.	Any items, if required for proper functioning and running of the machine that is not quoted			
	or mentioned in specification/ BoQ should be included and provided by vendor. Vendor			
	should include the cost of those items in price bid. Inclusion of such items will be			
1.0	responsibility of vendor.			
12.	In case the local representative (agency/supplier) of manufacturer changes, it shall be			
	responsibility of manufacturing company to run machine till its full life. Manufacturer must			
	submit declaration for this.			



S.N	Technical Specification
13.	Networking and configuration with existing Brachyrherapy machines (Make:Bebig),
	CTSimulator (Make:Philips, Brilliant Big bore) and/or proposed to be procured
	CTsimulator, equipment should be done by vendors at their own cost. No additional
	payment will be made to vendor for this work.
14.	The company should be responsible for installation and maintenance of the machine,
	software, accessories and networking which will help directly and indirectly in proper
	functioning of the machine.
D.	Accessories to be Supplied
1.	Chiller / Water Cooling system:-
	i. Supply, installation and maintenance of adequate Chiller system is responsibility of
	Company / bidder. Chiller space will be provided by hospital
	ii. Adequate Air condition for Linac room, console, and server as per machine and TPS as
	room requirements should supply.
	iii. Relative Humidity: Approx.50-55 RH or as per machine requirements
	m. Relative Humidity. Approx.30-33 KH of as per machine requirements
,	
	iv. Air Changes –more than 8 air changes per hour.
2.	On-Line UPS to run entire system minimum 30min (standby) must be supplied. The
	installation and maintenance should be done by bidder.
	a) Machine must fit in the Bunker of dimension as per attached drawings.
	b) Radiation beam centre must be in the midline ±60cm of the existing primary wall length
	(gantry-target direction)
3	c) Must have adequate clearance with walls for all couch movements as per offered machine
	standard.
	d) Additional modifications including all complete work (civil electrical plumbing etc) as
	required to install the Linac shall be the bidder's responsibility.
	e) All Internal decoration and furnishing of bunker, control console, TPS, server room
	(flooring, painting, , networking, wiring, room lights, false walls and ceiling) shall be the
	responsibility of bidder.
	f) Dismantle of existing 600CD machine including base frame shall be the responsibility of
	bidder.
	g) Pit preparation and base frame installation if required as per quoted model, shall be the
	responsibility of bidder.
	h) Modification of existing internal dimensions of bunker shall not be permitted. For
	radiation safety requirement, if required, outer wall retrofit is allowed.
	i) Existing bunker door replacement/repair shall be bidder's responsibility.
4	j) For site/ bunker details bidder may visit the site.
4	Dosimetry(BeamScan ) kit for Machine commissioning
	a) Kit (Part number: T41043.1.270)
	b) BeamDose software (Reference number: \$080053
	c) One day on-site hardware and software application training



S.N	Technical Specification					
	Training Manufacturing site/ company training center					
5						
	1. Two Radiation Oncologists and two Medical Physicists: Training on TPS workflow					
	(basic, tools, contouring, planning, verification) for one week					
	2. Training for 2 radiotherapy technologist for one week					
	3. Medical Physicist (i) TPS, data administration, Record &verification: one week and					
	(ii) Machine commissioning: one week					
	4. Training for a biomedical engineer in company training center for one week					
	5. Onsite Basic operation of Linear Accelerator: one week training to Radiation					
	Technologist and Medial Physicist					
	All the financial liabilities shall be borne by the bidder including transportation, lodging, and					
	accommodation.					
	Training schedules should be matched and approved by hospital.					

#### **Bill of Quantity**

I	Training Manufacturing site/ company training center	
	Two Radiation Oncologists and two Medical Physicists: Training on TPS workflow (basic, tools, contouring, planning, verification) for one week	
	2. Training for 2 radiotherapy technologist for one week	
	3. Medical Physicist (i) TPS, data administration, Record &verification: one week and (ii) Machine commissioning: one week	
	4. Training for a biomedical engineer in company training center for one week	
	5. Onsite Basic operation of Linear Accelerator: one week training to Radiation Technologist and Medial Physicist	

II	Description	U	Qty	Remark
		n		
		it		



A	CIVIL STRUCTURAL WORKS AND INTERIOR			
A1	Dismantling Works inside Bunker, Console Room and	S	650	
	TPS room including machine, PCC, flooring, false	q		
	ceiling, walls, Furnitures, etc to any depth/width,	m		
	disposal of debris, cleaning & making the surface free			
	from dust and debris as per instruction. (Measurement			
	on floor area)			
A2	Supply and install 3 mm thick homogeneous anti-static	S	650	
	vinyl flooring with 0.3 mm wear layer, surface	q		
	resistivity $10^6$ – $10^9 \Omega$ , smooth non-slip finish, light	m		
	neutral color, seamless welded joints with conductive			
	adhesive, grounded to building ESD system, including			
	150 mm matching skirting, installed over self leveling			
	compound, moisture-free concrete subfloor, resistant			
	to rolling loads, disinfectants, fully compliant with			
	IEC 61340-5-1 and ASTM F150 standards			
A3	Wall finishing with medical-grade emulsion paint with	S	3000	
	minimum two coats of washable paint over primer and	q		
	putty (location: bunker, console room, TPS room)	m		
A4	Supply and install 600×600 mm mineral fiber	S	300	
A4	Supply and install 600×600 mm mineral fiber		300	
	ceiling/wall tiles, 15–20 mm thick, fire-resistant Class	q		
	B1, with smooth light-colored finish, high sound absorption (NRC $\geq$ 0.6), moisture-resistant, dust-	m		
	proof, ESD-safe, laid on powder-coated GI T-grid			
	framework with adjustable hangers, perimeter			
	channels, and access panels, allowing integration with			
	lighting, HVAC diffusers, and electrical services,			
	ensuring easy maintenance and compliance with			
	hospital safety standards			
A5	Radiation Bunker Door servicing/replacement with	N	1	
	interlock provision as per requirement of OEM.	0	1	
	interfock provision as per requirement of OEIVI.	s		
В	FURNITURE WORKS	3		
B1	Supplying and applying medical graded vinyl wall	S	50	
וע	cladding in bunker corners		30	
	cladding in bulker corners	q m		
B2	Supply and installation of ergonomic workstation	S	19	+
D2	tables (width 2'8") with 25–30 mm solid hardwood top		1)	
	finished with durable laminate, solid hardwood frame	q m		
	and legs, edge-banded, lockable 2–3 drawer units with	111		
	solid wood fronts and smooth sliding mechanisms,			
	cable management provisions(modular design) as per			
	instruction (measurement shall be made in as Length*			
	height) as per instruction.			
	neight) as per histraction.			



В3	Wall-mounted storage cupboards with width (1'6") made up of minimum 19mm thick premium plywood or solid wood body and shelves, lockable doors, antitip design with laminated finish within LINAC room; to store: Dosimetry & QA Items, LINAC accessories. (measurement shall be made as Length* height) as per instruction.	s q m	6	
B4	Wooden Tables for Workstations with overhead cabinets of width 2' (19mm premium laminated plywood) (measurement shall be made as Length* height) as per instruction.	s q m	10	
B5	Ergonomic office Revolving chairs with adjustable height, backrest and handrest, 360° swivel, high-density foam seat and backrest as per instruction.	n o s	10	
В6	Supply and install metal visitor chair with a durable powder-coated steel frame, ergonomic backrest and seat with a minimum width of 18–20 inches, arranged in rows or clusters, suitable for high-traffic hospital waiting areas as per instruction	n o s	40	
С	ELECTRICAL WORKS			
C1	Main Power Supply & Distribution – 3-phase, 400V, 50Hz with MCBs, isolators, busbar, panel board, and earthing	L S	1	For LINAC machine & associated systems
C2	UPS & Backup Power – Online UPS for critical equipment including battery bank and installation	L S	1	30 min backup depending on requirement
СЗ	Emergency Generator Connection – Cabling, ATS, and connection to hospital DG set	L S	1	For uninterrupte d LINAC operation
C4	Room Lighting & Power Points – LED lighting, switches, sockets for consoles, TPS, and auxiliary equipment rooms	L S	1	Adequate illumination & power for staff workstation s
C5	Dedicated Circuits for LINAC Ancillaries – Cooling pumps, chiller, HVAC system, computer consoles, motorized patient table, safety interlocks	L S	1	As per OEM recommend ation
C6	Earthing & Lightning Protection – Earthing pits, bonding of all metallic structures, lightning arrestor	L S	1	As per requirement s Critical for sensitive electronic equipment




C7	Cable Trays & Conduits – For power, data, and	L	1	Neat
C/	control cables including trays, conduits, and supports	S	1	installation
	control cables including trays, conduits, and supports	3		for safety &
				maintenanc
				e
C8	Fire Alarm & Safety Integration – Smoke detectors,	L	1	Mandatory
	emergency lights, and integration with hospital fire	S		for safety
	alarm system			compliance
C9	Testing & Commissioning – Electrical testing,	L	1	As per
	insulation resistance test, earth continuity, functional	S		hospital &
	testing of all circuits			OEM
D	HVAC WORKS			standards
D1	Ductable A/C units along with Low side works and	T	11+	
וע	=	R		
	high side works for complete installation &	IX.	Adequat	
	commissioning of AC		e	
	Supply, installation, testing & commissioning of		number	
	aircooled ductable split air conditioner with ceiling		for	
	suspended IDU and all standard fitting,GSS sheet		proper	
	metal duct(insulation using resin bounded glass wool		functioni	
	with 7 micron aluminium foil) for air distribution		ng of the	
	22/24 G, IDU SS drain pan as per specification		entire	
	complete with suitable capacity drive motor,		system	
	aircooled condensor with all accessories ,hermetically			
	sealed scroll compressor, electronic microprocessor			
	pendant controller with digital display, first charge			
	refrigerant gas, vibration isolator pads, structural			
	support for fixing IDU/ODU, safety devices including			
	thermal protector, pressure release valve ,overload			
	relay single phase preventer etc, power wiring and			
	control cabling(indoor to outdoor), thermostat wiring,			
	high-low pressure cut out suitable for 3 phase 440V			
	supply etc complete as required) for Bunker 5.5 TR			
	working and 5.5 TR as standby, for console room, 2			
	TPS rooms, server room and UPS room as required			
	Make: Daikin, Hitachi, Blue Star, Voltas			
D3	Supply and install industrial-grade dehumidifier, floor-	L	2	
	standing or wall-mounted type, with automatic	S		
	humidity control (maintaining 45–55% RH), capacity			
	as per room volume and load, washable air filters,			
	digital display, continuous drainage connection, low-			
	noise operation (<50 dB), corrosion-resistant body,			
	energy-efficient compressor with auto-defrost, and			
	complete with power connection, installation, testing,			
	and commissioning as per hospital and OEM			
	standards.			
<u> </u>	SWITCHIE GO.			



E	PLUMBING WORKS			
E1	Supply, installation, testing, and commissioning of	L	1	
	complete plumbing works including incoming water	S		
	supply connection with valves and backflow			
	prevention, internal cold/hot water distribution,			
	drainage and sewer connections with traps and floor			
	drains, condensate drains for HVAC/chiller, sanitary			
	fixtures (basins, sinks, hose bibs), neutralization pit (if			
	required), pipe supports, insulation, storm water			
	provision, corrosion protection, coordination with			
	civil/electrical works, and all accessories, fittings,			
	testing, disinfection, documentation, and handover as			
	per hospital standards			
F	FIRE & SAFETY			
F1	Fire Alarm System with smoke detectors as per	L	1	
	standards	S		
F2	Fire extinguishers (CO <sub>2</sub> / clean agent) in bunker &	N	3	
	console as per standards	О		
		S		
F3	Emergency lighting & exit signage in bunker &	L	1	
	console as per standards	S		

600CD Bunker





Interested firm/company can submit their detail proposal with breakdown of the equipment with related goods/Services/Wokr to the hospital and make administration directly or via email: <a href="mailto:bpkmchhospital@gmail.com/bpkmchprocurement@gmail.com/bpkmchpkmchprocurement@gmail.com/bpkmchpkmchpkmchpkmchpk